

Gamme ADES LED SMD



232905
252905

232903



332903
333903



433903



433933



Code	Gencod	LED par lampe	Voltage	Durée de vie	Puissance	Culot	Temp. de couleur	Angle faisceau	Classe énergie	Lumen	Equ. Incan.	Dim.	U.V.	Cdt.
SMD Standard *M* dépolie														
232905	325341232905 5	30	230	30 000H	5W	E 27	3000k	120°	A	420	37w	85 x 55	Blister x 1	05 / 20
252905	325341252905 9	30	230	30 000H	5W	E 27	6000k	120°	A	450	39w	85 x 55	Blister x 1	05 / 20
SMD Standard dépolie														
232903	325341232903 1	20	230	30 000H	3W	E 27	3000k	120°	A	250	25w	96 x 55	Blister x 1	05 / 20
SMD Sphériques dépolies														
332903	325341332903 0	20	230	30 000H	3W	E 27	3000k	120°	A	250	25w	72.5 x 45	Blister x 1	05 / 20
333903	325341333903 9	20	230	30 000H	3W	E 14	3000k	120°	A	250	25w	72.5 x 45	Blister x 1	05 / 20
SMD Flamme dépolie														
433903	325341433903 8	20	230	30 000H	3W	E 14	3000k	120°	A	250	25w	94 x 37	Blister x 1	05 / 20
SMD Flamme CV dépolie														
433933	325341433933 5	20	230	30 000H	3W	E 14	3000k	120°	A	250	25w	132 x 37	Blister x 1	05 / 20

DOC LED SMD CT082011

La durée de vie annoncée est donnée à titre indicatif et est susceptible de varier en fonction de la tension d'alimentation et des conditions d'utilisation.